

PARTIAL STORAGE HEATER



Advantages:

- **Ease of Installation**
- **Safe, clean and easy to operate**
- **Slimline Radiators are 70 mm deep**
- **No maintenance required**
- **100% efficient**
- **No boiler, plumbing or pipe work required**

Type TT-KS N

- Our „Low“ model
- Fully controllable by either manual or digitally controlled thermostats with „open window function, adaptive start function and more...“)
- Radiators come fully assembled with appropriate plugs and 1.5m of cable
- All radiators are powder coated in a white high quality enameled finish
- Castors, feet stands or radiator supports can be ordered as optional extras

Using mobile:

This product is only suitable for well-insulated rooms or for occasional use.



Our „Low“
Height: 34 cm
Depth: 7 cm

Standard control



| Type | Power [Watt] | Dimensions [cm] | Protection class |
|--|--------------|-----------------|------------------|
| TT-KS 800 N DSM RF X4 | 800 | 68 x 34 x 7 | IP 20 IP 24 |
| TT-KS 1200 N DSM RF X4 | 1200 | 68 x 34 x 7 | IP 20 IP 24 |
| TT-KS 1600 N DSM RF X4 | 1600 | 128 x 34 x 7 | IP 20 IP 24 |
| TT-KS 2000 N DSM RF X4 | 2000 | 158 x 34 x 7 | IP 20 IP 24 |
| s= Standard DSM = „DSM“-Thermostat RF = RF Receiver X4 = protection class IP 24 | | | |

- elegant finish safe, clean and easy to serve
- Fully controllable by either manual or digitally controlled (DSM) thermostats
- Just 70 mm deep
- No maintenance required
- 100% efficient
- Radiators come fully assembled with appropriate plugs and 1.5m of cable
- Castors, feet stands or radiator supports can be ordered as optional extras

With receiver RF



With „DSM“ - 24/7 digital programmable electronic thermostat, open window function, internet adjustable etc..



TECHNOTHERM a brand of Lucht LHZ GmbH & Co. KG
Reinhard-Schmidt-Str. 1 | 09217 Burgstädt
Telefon: +49 (0) 3724 66869 0
Telefax: +49 (0) 3724 66869 20
info@technotherm.de | www.technotherm.de

Subject to errors and technical amendments. Dimensions without guarantee! Edition 04/18