

## DIRECT HEATER



### Advantages:

- Twin overheat protection
- High Quality Aluminum grill for easy cleaning
- Precision German quality engineering and manufacturing
- Special ceramic inlay

### Type: CPH Wall Convector

- Outputs up to 2.4kW
- Patented heat retention tablet delivers greater energy efficiency than a traditional convector heater
- Available with manual Thermostat and On Off switch
- High quality stainless steel element prevents rusting
- Wall mounted or free-standing option available
- IP 24 drip proof for use in wet areas



Device on feet:

This product is only good for isolated rooms or for occasional use.

Our „Wall Convector“ CPH  
Height: 45 cm  
Depth: 9 cm



With electronic room temperature control



Typenreihe	Leistung [Watt]	Abmessungen [mm] B x L x T	Schutz- klasse
CPH 1000	1000	415 x 445 x 85	IP 24
CPH 1500	1500	565 x 445 x 85	IP 24
CPH 2000	2000	695 x 445 x 85	IP 24
CPH 2400	2400	915 x 445 x 85	IP 24
CPH 1000 E	1000	415 x 445 x 85	IP 24
CPH 1500 E	1500	565 x 445 x 85	IP 24
CPH 2000 E	2000	695 x 445 x 85	IP 24
CPH 2400 E	2400	915 x 445 x 85	IP 24
E = with electronic room temperature control			