

DIRECT HEATING




Advantages:

- Infrared technology
- Chrome-nickel heating element is unbreakable
- Fast heat
- 3-stage switchable

Chirch Pew KBR

- Infrared Chirch Pew
- 3-stage switchable 1/3, 2/3 and 3/3
- Connection on both sides
- Complete with feet and protective housing
- Color similar to RAL 1019
- powder coated
- Special sizes and colors possible



Pew heating KBR adjustable with the Thermostat KRT



Information:

The corresponding insulating plates are required for installation between the bottom of the bench and the heater.

Temperature control KRT: optional

- For Church Pew KBR, with digital display, temperature control. For switching the heating in stages: 1/3, 2/3 and 3/3. Target, and actual temperature to maintain the desired temperature. No overheating in the banking area. Single function and switching groups possible.

Type	Power [Watt]	Dimensions [cm]
KBR 6/25	250	600 x 100 x 19
KBR 8/35	350	800 x 100 x 19
KBR 10/45	450	1000 x 100 x 19
KBR 12/55	550	1200 x 100 x 19
KBR 14/65	650	1400 x 100 x 19
Isolation boards UPK		
UPK 6/6		600 x 250 x 6
UPK/ 8/6		800 x 250 x 6
UPK 10/6		1000 x 250 x 6
UPK 12/6		1200 x 250 x 6 2-parts
UPK 14/6		1400 x 250 x 6 2-parts
Controllable with the temperature controller KRT		