



Storage Heater TTB-E Duo

Electric - Storage Heater with static heat emission and room temperature control thermostat

Storage Heater TTB-E Duo

Simply installation with unique housing design

The storage heater outside casing comes in one piece. Only two screws at the front need to be inserted which creates an easy installation process.

Main points:

- 4 different sizes from 0,85 kW up to 3,4 kW
- Depth 18,5 cm, height 71,5 cm
- With special accessories wall mounting possible
- Extra heat will be released with the unique discharge control

controlled heat transfer with a patented venting system

top mounted electronic thermostat with "intelligent-self-learning" input control and 24/7 output control

inside brick packs made from Ferolite for heat storage

smooth surface easy to clean

insulation from Vermiculit/Microtherm

direct acting aluminium heating element

2 feet (included)

Only 18,5 cm deep - universal application

Due to the slim depth of Static Storage Heaters the heating system can be easily installed with the wall mounting or with the available free standing options.

Storage heater with electronic control:

Storage heater of the type TTB-E Duo Technotherm with static heat emission are ideal as a heating device for many types of rooms within a home. It measures the room temperature and decides on the duration of the charge. This saves money!

TTB Storage Heater Supply voltage: 230V 1N ~ 50Hz	power input [Watt]	weight body [kg]	weight bricks [kg]	weight total [kg]	additional direct Heating Element	dimensions WxHxD [mm]	article number
TTB-E Duo 8+	850	18	30	48	500 W	465 x 715 x 185	842 508 007
TTB-E Duo 17+	1700	27	59	86	500 W	675 x 715 x 185	842 517 007
TTB-E Duo 26+	2550	35	89	124	750 W	885 x 715 x 185	842 526 007
TTB-E Duo 34+	3400	44	118	162	750 W	1095 x 715 x 185	842 534 007

Key features design TTB-E Duo:

- Built-in Electronic thermostat for input and output control
- Only 18,5 cm depth - ergonomic and robust
- Easy installation
- Controlled heat emission with a patented venting system
- Suitable for 8 to 16 hours charge time
- Silent radiant and convected heat emission
- Corresponding safety standard EN 6033, Safety Class 1
- Colour RAL 9003
- Control of room temperature depending on the charging
- Additional: "direct acting" aluminium heating element



Innovative technology in perfect shape

Static storage heater characterizes the controllable production of heat without annoying fan noise. By using mild radiant heat and natural heat convection, these heaters are especially good in living rooms and larger bedrooms. Other application areas are corridors and offices where comfortable simple heat is desired. Static Storage Heaters operate silently and cleanly.



TECHNOTHERM a brand of Lucht LHZ GmbH & Co. KG
Reinhard-Schmidt-Str. 1 | 09217 Burgstädt
Telefon: +49 (0) 3724 66869 0
Telefax: +49 (0) 3724 66869 20
info@technotherm.de | www.technotherm.de

Errors and technical changes reserved. Dimensions without guarantee! Edition 09/19